

## C-M Rohr-Anschlusssteile Überwurfmutter für 24° Anschluss



CF-D  
CF-DPR

Reihe	PN [bar]		ØD <sub>1</sub> [mm]	T	L <sub>1</sub> [mm]	S <sub>1</sub> [mm]	Bestellnummer *	kg/ 100
	C	CF						
LL	100	100	4	M8x1	11,0	10	<b>C-M 04 LL X</b>	0,4
			6	M10x1	11,5	12	<b>C-M 06 LL X</b>	0,6
			8	M12x1	12,0	14	<b>C-M 08 LL X</b>	0,7
			10	M14x1	12,5	17	<b>C-M 10 LL X</b>	1,1
			12	M16x1	13,0	19	<b>C-M 12 LL X</b>	1,3
L	315	500	6	M12x1,5	14,5	14	<b>C-M 06 LX</b>	0,3
			8	M14x1,5	14,5	17	<b>C-M 08 LX</b>	1,4
			10	M16x1,5	15,5	19	<b>C-M 10 LX</b>	1,7
	315	400	12	M18x1,5	15,5	22	<b>C-M 12 LX</b>	2,4
			15	M22x1,5	17,0	27	<b>C-M 15 LX</b>	4,0
			18	M26x1,5	18,0	32	<b>C-M 18 LX</b>	5,8
	160	250	22	M30x2	20,0	36	<b>C-M 22 LX</b>	7,9
			28	M36x2	21,0	41	<b>C-M 28 LX</b>	9,1
			35	M45x2	24,0	50	<b>C-M 35 LX</b>	13,5
42			M52x2	24,0	60	<b>C-M 42 LX</b>	21,6	
S	630	800	6	M14x1,5	16,5	17	<b>C-M 06 SX</b>	1,6
			8	M16x1,5	16,5	19	<b>C-M 08 SX</b>	1,9
			10	M18x1,5	17,5	22	<b>C-M 10 SX</b>	2,9
	630	630	12	M20x1,5	17,5	24	<b>C-M 12 SX</b>	3,3
			14	M22x1,5	20,5	27	<b>C-M 14 SX</b>	5,0
	400	630	16	M24x1,5	20,5	30	<b>C-M 16 SX</b>	6,4
	400	400	20	M30x2	24,0	36	<b>C-M 20 SX</b>	10,0
			25	M36x2	27,0	46	<b>C-M 25 SX</b>	20,6
	250	400	30	M42x2	29,0	50	<b>C-M 30 SX</b>	22,3
			38	M52x2	32,5	60	<b>C-M 38 SX</b>	32,0

\*Wenn Sie Stahl benötigen, ersetzen Sie bitte die Kennbuchstaben **C** durch **CF**!  
C = Edelstahl, 1.4571 CF = Stahl verzinkt Cr(VI)-frei

my-hydraulik24.de  
Hydraulik einfach online kaufen